



## AT6000

Suitable for personal and commercial use

### Feature:

- Advanced Flat-Surfaced Alcohol Sensor
- Energy saving & Environment friendly
- Quick response and resume
- SMD assembling, Smart MCU control, stable performance
- Direct testing process big LCD indication
- Digital LCD display with light blue backup
- Portable and fashion design, sterilized mouthpieces
- Audio warning beyond pre-set limit
- Sensor Fault Self checking
- Battery saved design, low voltage indication
- Car cigarette lighter optional

**Certificate:** CE and RoHS

**Package:** In colorful giftbox package, 50PCS packed in one carton

**Carton size:** 33x39x45cm,  
Gross Weight : 10.00KGS(Approx)

**Standard:** Colorful Giftbox, Operation Manual, 5 Mouthpieces

**Optional:** Batteries

### Specification:

- Sensor type: Flat-Surfaced Alcohol Sensor
- Working Voltage: DC4.5V (3×AAA) Batteries
- Working Current: ≤120mA
- Working Environment:  
Temperature -10℃~50℃  
Relative Humidity ≤95% No Dews
- Detection Range: 0.00~1.00mg/L;  
0.00~0.20%BAC;  
0.00~2.00g/L;  
0.00~2.00%BAC
- Alarming Level: 0.25mg/L (0.05%BAC,  
0.50g/L; 0.50%BAC)
- Accuracy: ±10% F.S
- Response Time: <5s
- Resume Time: ≤20s
- Display: 3 digits LCD display with light blue backup
- Dimension: 103×65×27mm (L×W×H),  
≤64 g Battery excluded
- Battery expectancy time: ≥200Times



AT6000

## AT6100

Suitable for personal and commercial use



AT6100

### Feature:

- Advanced Flat-Surfaced Alcohol Sensor
- Energy saving & Environment friendly
- Quick response and resume
- SMD assembling, Smart MCU control, stable performance
- Direct testing process big LCD indication
- Digital LCD display with light blue backup
- Portable and fashion design, Healthy anti-suck mouthpiece
- Audio warning beyond pre-set limit
- Sensor Fault Self checking
- Battery saved design, low voltage indication

**Certificate:** CE and RoHS

**Package:** In colorful giftbox package, 50PCS packed in one carton

**Carton size** is 33x39x45cm,  
Gross Weight is 10.00KGS/Carton (Approx)

**Standard:** Colorful Giftbox, Operation Manual, 5 Mouthpieces

**Optional:** Batteries

### Specification:

- Sensor type: Flat-Surfaced Alcohol Sensor
- Working Voltage: DC4.5V (3×AAA) Batteries
- Working Current: ≤120mA
- Working Environment:  
Temperature -10℃~50℃  
Relative Humidity ≤95% No Dews
- Detection Range: 0.00~1.00mg/L;  
0.00~0.20%BAC;  
0.00~2.00g/L;  
0.00~2.00%BAC
- Alarming Level: 0.25mg/L (0.05%BAC,  
0.50g/L; 0.50%BAC)
- Accuracy: ±10% F.S
- Response Time: <5s
- Resume Time: ≤20s
- Display: 3 digits LCD display with light blue backup
- Dimension: 100×70×28mm (L×W×H),  
≤65 g Battery excluded
- Battery expectancy time: ≥200Times