

4 CHANNEL WALL MOUNT CONTROLLER

Gas Detection for Life

Beacon 410 Model



Features

- Digital display of all 4 channels
- Accepts direct connect sensors for LEL / O₂ / H₂S / CO / CO₂
- Accepts any 4-20 mA transmitter, 2 or 3 wire
- 3 programmable alarm levels per channel
- Up to 3 configurable alarm relays per channel
- Zero follower automatically compensates sensor drift
- 4-20 mA analog & Modbus digital output standard
- 115 / 220 VAC or 24 VDC operation
- Audible alarm with silence feature
- Alarm reset switch
- Built in trouble alarm with relay
- Weather proof NEMA 4X enclosure
- Optional strobe & battery backup available

Applications

- Petrochemical plants
- Refineries
- Water & wastewater treatment plants
- Pulp & paper mills
- Gas, telephone & electric utilities
- Parking garages
- Manufacturing facilities
- Steel
- Automotive
- HVAC

The Beacon 410 is a highly configurable, microprocessor-based, flexible and easy to use 4 channel gas monitor. It simultaneously displays the gas type, readings, and status for 4 channels of gas detection. It can monitor any combination of direct connect sensors (LEL combustibles, Oxygen, Hydrogen Sulfide, Carbon Monoxide, and Carbon Dioxide) as well as any 4-20mA transmitters.

Each channel has 3 fully configurable alarm points. **A built-in** silenceable audible alarm alerts you to alarm conditions. Each channel also has 2 dedicated fully configurable relays and there is a bank of common relays as well. The common relays can optionally be configured as additional channel relays allowing up to 3 **alarm relays per channel**.

Each channel provides a 4-20mA output signal. A digital **Modbus** interface for remote logging of data via a Modbus network is standard. A Min-Max feature retains high & **low peak readings** for review at any time.

Field calibration is made simple by the easy to use Calibration **Mode**. **A fully configurable high visibility strobe is available as an option**. The unit can be powered from 115/220 VAC, **an external** 24 VDC source, or a 24 VDC backup battery. **A trickle** charging battery backup feature is also available as an option.

All features and functions of the Beacon 410 are controlled by easy to use menus on the backlit LCD display. **The form-C (SPDT) relay contacts** are rated at 10A, 250V, reducing or eliminating the need for additional slave relays. All features of the Beacon 410 are built into the unit so you never need to purchase or maintain any "add-on" cards or components.



RIKEN KEIKI

Beacon 410 Model

Physical	
Dimensions:	Height 216mm Width 178 mm Depth: 109 mm
Enclosure:	NEMA 4X non-metallic for indoor and outdoor locations
Conduit Connection:	3/4" NPT conduit hubs, 4 provided, for sensor, power and relay wiring.
Wiring Termination:	Screw type terminal block, 14 gauge max.
Power:	115 VAC & 220 VAC, or 24 VDC nominal. Battery backup option available.
Controls:	Display PCB Control switches: <ul style="list-style-type: none">• UP/YES push button switch• ESCAPE push button switch• External reset switch• DOWN/NO push button switch• ENTER push button switch• On/Off toggle switch
Environmental	
Operating Temp:	-20°C to 50°C
Storage Temp:	-20°C to 70°C
Relative Humidity:	0 – 95% RH (non-condensing)
Enclosure Rating:	NEMA-4X enclosure, waterproof, chemical and weather resistant.
Inputs	
Direct Wired Sensors:	LEL, Oxygen, Carbon Monoxide, Hydrogen Sulphide, and Carbon Dioxide. Remote amp not required for less than 500 feet.
4-20 mA Sensors:	Accepts any 4-20 mA transmitters (24 VDC, 2 or 3 wire). A wide variety of RKI/Riken sensors are available with 4-20 mA signals. Wiring distances up to 5,000 metres.
Sampling methods:	Diffusion and sample draw heads available.
Outputs	
Relays:	Two flexible, programmable Form-C (C, NO, NC) relays per channel, plus five common relays (Fail, Alarm-1, Alarm-2, Alarm-3, Alarm-Any). Common relays may optionally be assigned to function as additional channel alarm relays, providing for up to three alarm relays per channel. 10A contact rating.
4-20 mA:	Signal output, 4-20 mA (maximum load impedance 500 ohms), per channel
RS-485:	Modbus format RS-485 serial output of all channel data, including gas reading and alarm status.
Display:	4 x 20 backlit LCD display
Audible:	Built-in audible alarm, 94 dB, mounted on enclosure. Coded output: Pulsing = gas alarm, Steady = fail
Visual:	<ol style="list-style-type: none">Alarm LED's (on Display PCB)<ul style="list-style-type: none">• Alarm 1, yellow• Alarm 2, orange• Alarm 3, red• Fail, yellowGreen pilot LED to indicate AC power connected (on Display PCB)An optional 24 VDC NEMA 4X strobe mounted to top of case
Warranty:	One year materials and workmanship.

AUSTGAS Instrument Services Pty Ltd

13 Greer St
Bonnyrigg Heights NSW 2177
AUSTRALIA

Phone: +61 2 9823 2551
Fax: +61 2 9822 9284
Mobile: +61 451 304 884
Email: austgas@hotmail.com